



Shell ALEXIA S6

- ULTIMATE PROTECTION
- HIGH PERFORMANCE

Cylinder Lubricant for two-stroke low speed diesel engines

Shell Alexia S6 is a cylinder lubricant designed for use in two-stroke low speed diesel engines running under conditions of extreme oil stress. It provides additional protection in engines that require a very high performing product and is suitable for use with engines burning residual fuel with Sulphur levels >1.0%. It has been engineered to offer excellent performance for the new, more demanding engines, under challenging operational conditions such “slow” and “flexible” steaming regimes and high fuel Sulphur levels.

Shell Alexia S6 utilises Shell’s unique triple action technology to give advanced protection for engines experiencing cold corrosion, such as Tier II tuned engines and those retrofitted with turbocharger cut-out, where additional support from the lubricant is required. It has been especially formulated to deal with all aspects of Oil Stress.

Shell Alexia S6 has a BN of 100 and is an SAE50 oil cylinder lubricant.

DESIGNED TO MEET CHALLENGES

Performance, Features & Benefits

- **Engine protection**

Shell Alexia S6 offers outstanding acid neutralising properties which help to prolong the life of components.

It has superior deposit control and minimises deposit build up on pistons, piston rings, ring grooves, under piston spaces and in cylinder ports.

Shell Alexia S6 has been especially designed for the most demanding engines and operating conditions, where significantly more protection from the lubricant is required.

Shell Alexia S6 builds on the Shell Alexia S4 and Shell Alexia S5 technology to extend the portfolio with a product that utilises Shell’s unique triple action technology that is designed to give advanced protection for engines experiencing cold corrosion. It is formulated to combat all aspects of oil stress.

Main Applications

- **Two-stroke low speed diesel engines**

Cylinder lubrication of two-stroke low speed diesel engines running under conditions of very high oil stress (for example, engines with very long strokes or fitted with turbocharger cut out) and burning residual fuel oil with Sulphur > 1.0%.

For HFO use in the lower Sulphur range, it is recommended that the results from onboard (such as Shell Analex Alert and Shell Onboard+) and onshore used oil analysis (such as Shell RLA) are used, in conjunction with inspections, to determine whether it would be beneficial to switch to Shell Alexia S4. This is particularly important when running under full load conditions, in combination with the lower fuel Sulphur levels.

Specifications, Approvals & Recommendations

- **Approvals**

Shell Alexia S6 has been approved for use in:

- MAN B&W two-stroke engine designs (provided that the recommendations in engine type specific guidelines are followed).
- Wärtsilä two-stroke engine designs (provided that the recommendations in engine type specific guidelines are followed).
- MHI two-stroke engine designs (provided that the recommendations in engine type specific guidelines are followed).
- **Cylinder oil feed rates**

Insufficient cylinder oil feed rates can lead to corrosive wear, seized and broken rings and consequent blow-by and scavenge fire risks, and to the formation of excessive deposits.

The feed rate should be determined in accordance with OEM guidelines and should then be further optimised using a combination of onboard analysis (such as Shell Analex Alert and Shell Onboard+) and onshore used oil analysis (such as Shell RLA), in conjunction with engine inspections.

- Shell Alexia S6 has a BN of 100 and is an SAE50 viscosity grade.

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Help Desk.

Compatibility & Miscibility

• Mixing of cylinder lubricants

Shell Alexia S6 is fully miscible with all other cylinder lubricants. However, for optimum performance, Shell Alexia S6 should not be used in conjunction with any other cylinder lubricant.

Typical Physical Characteristics

Properties	Method	Shell Alexia S6
SAE Viscosity Grade		50
Viscosity Index	ASTM D2270/ IP 226	>95
Density @15°C kg/l	ASTM D4052/ IP 365	0.954
Flash Point (Closed) Pensky Martens °C	ASTM D93/ IP 34	>210
Pour Point °C	ASTM D97/ IP 15	<-6
BN mg/KOH/g	ASTM D2896/ IP276	100
Sulphated Ash % wt	ASTM D874/ IP163	12.1

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

• Health and Safety

Shell Alexia S6 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from www.epc.shell.com

• Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Additional Information

• Advice

Advice on applications not covered here may be obtained from your Shell representative.