

Safety Data Sheet

Shell Special Fuel Oil

Version 2.0

Revision Date 22.07.2015

Print Date 23.07.2015

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Shell Special Fuel Oil

Product code : 002D2418

Manufacturer or supplier's details

Supplier : Pilipinas Shell Petroleum Corporation
156 Valero St. Salcedo Village
1227 Makati

Telephone : (+63) 28027600

Telefax : (+63) 28166565

Emergency telephone number : +632 8027600

Email Contact for Safety Data Sheet : If you have any enquiries about the content of this SDS please email fuelSDS@shell.com

Recommended use of the chemical and restrictions on use

Recommended use : Fuel for use in off-road diesel engines, boilers, furnaces and other combustion equipment.

Restrictions on use : This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier.

2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 4
Carcinogenicity : Category 1B
Acute toxicity (Inhalation) : Category 4
Reproductive toxicity : Category 2
Specific target organ toxicity - repeated exposure : Category 2 (Blood., Liver., thymus)
Acute aquatic toxicity : Category 1
Chronic aquatic toxicity : Category 1

GHS Label element

Hazard pictograms : 

Signal word : Danger

Hazard statements : PHYSICAL HAZARDS:
H227 Combustible liquid.
HEALTH HAZARDS:
H350 May cause cancer.
H332 Harmful if inhaled.
H361 Suspected of damaging fertility or the unborn child.

Safety Data Sheet

Shell Special Fuel Oil

Version 2.0

Revision Date 22.07.2015

Print Date 23.07.2015

H373 May cause damage to organs through prolonged or repeated exposure.

Blood.

Liver.

thymus

ENVIRONMENTAL HAZARDS:

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

:

Prevention:

P201 Obtain special instructions before use.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P273 Avoid release to the environment.

Response:

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

Disposal:

P501 Dispose of contents and container to appropriate waste site or reclaimer in accordance with local and national regulations.

Other hazards which do not result in classification

Hydrogen sulphide (H₂S), an extremely flammable and toxic gas, and other hazardous vapours may evolve and collect in the headspace of storage tanks, transport vessels and other enclosed containers. May ignite on surfaces at temperatures above auto-ignition temperature. This material is a static accumulator. Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Not classified as flammable but will burn. Flammable vapours may be present even at temperatures below the flash point. Therefore it should be treated as a potentially flammable liquid. Contact with hot material can cause thermal burns which may result in permanent skin damage.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Chemical nature : Streams obtained from distillation and cracking processes and containing a mixture of saturated, aromatic and olefinic hydrocarbons with carbon numbers predominantly in the C₉ to C₅₀ range. Contains cracked components in which polycyclic aromatic compounds, mainly 3-ring but some 4 to 6 ring species, are present. Contains sulphur, oxygen, nitrogen compounds, vanadium and other metals at >10 ppm <500ppm w/w.

Safety Data Sheet

Shell Special Fuel Oil

Version 2.0

Revision Date 22.07.2015

Print Date 23.07.2015

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration [%]
fuel oil, residual	68476-33-5	Flam. Liq.4; H227 Asp. Tox.1; H304 Acute Tox.4; H332 Carc.1B; H350 Repr.2; H361 STOT RE2; H373 Aquatic Acute1; H400 Aquatic Chronic1; H410	100

Contains hydrogen sulphide, CAS # 7783-06-4.

For explanation of abbreviations see section 16.

4. FIRST-AID MEASURES

- General advice : Vapourisation of H₂S that has been trapped in clothing can be dangerous to rescuers. Maintain respiratory protection to avoid contamination from the victim to rescuer. Mechanical ventilation should be used to resuscitate if at all possible.
- If inhaled : Remove to fresh air. Do not attempt to rescue the victim unless proper respiratory protection is worn. If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting, or unresponsive, give 100% oxygen with rescue breathing or CPR as required and transport to the nearest medical facility.
- In case of skin contact : Cold product -
Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.
If persistent irritation occurs, obtain medical attention.
- Hot product -
If contact with hot product, immediately cool the burn area by flushing or immersing the affected area with water for at least 15 to 20 minutes. Do not attempt to remove anything from the burn area or apply burn creams or ointments. During transport do not cover the wound with dressing or sheet since these may adhere to the product.
- In case of eye contact : Cold product -
Flush eye with copious quantities of water.
If persistent irritation occurs, obtain medical attention.
- Hot product -
If contact with hot product, cool the burn area by flushing with large amounts of water for at least 15 minutes. Do not attempt to remove anything from the burn area or apply burn creams or ointments.
- If swallowed : If vomiting occurs spontaneously, keep head below hips to prevent aspiration.
Give nothing by mouth.

Safety Data Sheet

Shell Special Fuel Oil

Version 2.0

Revision Date 22.07.2015

Print Date 23.07.2015

- Most important symptoms and effects, both acute and delayed : Respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing.
Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision.
Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance.
- Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
- Notes to physician : Hydrogen sulphide (H₂S) - CNS asphyxiant. May cause rhinitis, bronchitis and occasionally pulmonary oedema after severe exposure. CONSIDER: Oxygen therapy. Consult a Poison Control Center for guidance.
Call a doctor or poison control center for guidance.

5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
- Unsuitable extinguishing media : Do not use direct water jets on the burning product as they could cause a steam explosion and spread of the fire.
Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.
- Specific hazards during firefighting : Hazardous combustion products may include:
A complex mixture of airborne solid and liquid particulates and gases (smoke).
Oxides of nitrogen
Oxides of sulphur.
Unidentified organic and inorganic compounds.
Flammable vapours may be present even at temperatures below the flash point.
The vapour is heavier than air, spreads along the ground and distant ignition is possible.
Will float and can be reignited on surface water.
Hydrogen sulphide (H₂S) and other toxic sulphur oxides may be given off when this material is heated. Do not depend on sense of smell for warning.
Carbon monoxide may be evolved if incomplete combustion occurs.
- Specific extinguishing methods : Use water spray to cool unopened containers.
Keep adjacent containers cool by spraying with water.
If possible remove containers from the danger zone.
If the fire cannot be extinguished the only course of action is to evacuate immediately.
Contain residual material at affected sites to prevent material

Safety Data Sheet

Shell Special Fuel Oil

Version 2.0

Revision Date 22.07.2015

Print Date 23.07.2015

from entering drains (sewers), ditches, and waterways.

Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : May ignite on surfaces at temperatures above auto-ignition temperature.
Do not breathe fumes, vapour.
Do not operate electrical equipment.

Environmental precautions : Take measures to minimise the effects on groundwater.
Contain residual material at affected sites to prevent material from entering drains (sewers), ditches, and waterways.
Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers.

Methods and materials for containment and cleaning up : Take precautionary measures against static discharges.
For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely Remove contaminated soil and dispose of safely.
For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely
Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers.

Avoid contact with skin, eyes and clothing.

Evacuate the area of all non-essential personnel.

Remove contaminated clothing.

Ventilate contaminated area thoroughly.

Observe all relevant local and international regulations.

Take precautionary measures against static discharges.

Additional advice : For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet.
Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.
For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.
Local authorities should be advised if significant spillages cannot be contained.
Maritime spillages should be dealt with using a Shipboard Oil Pollution Emergency Plan (SOPEP), as required by MARPOL Annex 1 Regulation 26.

7. HANDLING AND STORAGE

General Precautions : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet.
Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Prevent spillages.
Contaminated leather articles including shoes cannot be decontaminated and should be destroyed to prevent reuse.
Ensure that all local regulations regarding handling and storage facilities are followed.

Maintenance and Fuelling Activities - Avoid inhalation of vapours and contact with skin.

Advice on safe handling : Ensure that all local regulations regarding handling and storage facilities are followed.
The inherent toxic and olfactory (sense of smell) fatiguing properties of hydrogen sulphide require that air monitoring alarms be used if concentrations are expected to reach harmful levels such as in enclosed spaces, heated transport vessels and spill or leak situations. If the air concentration exceeds 10 ppm, the area should be evacuated unless respiratory protection is in use.
Avoid prolonged or repeated contact with skin.
When using do not eat or drink.
Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.
Earth all equipment.
Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.
Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.
Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.
If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.
Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges.
These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements.
These activities may lead to static discharge e.g. spark formation.
Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/s until fill pipe

Safety Data Sheet

Shell Special Fuel Oil

Version 2.0

Revision Date 22.07.2015

Print Date 23.07.2015

submerged to twice its diameter, then ≤ 7 m/s). Avoid splash filling.

Do NOT use compressed air for filling, discharging, or handling operations.

Avoidance of contact : Strong oxidising agents.

Product Transfer : Avoid splash filling Wait 2 minutes after tank filling (for tanks such as those on road tanker vehicles) before opening hatches or manholes. Wait 30 minutes after tank filling (for large storage tanks) before opening hatches or manholes. Keep containers closed when not in use. Refer to guidance under Handling section.

Storage

Other data : Drum and small container storage:
Drums should be stacked to a maximum of 3 high.
Use properly labeled and closable containers.
Prevent ingress of water.
Tank storage:
Tanks must be specifically designed for use with this product.
Bulk storage tanks should be diked (bunded).
Locate tanks away from heat and other sources of ignition.
Tanks should be fitted with heating coils.
Ensure heating coils are always covered with product (minimum 15 cm).
Electrostatic charges will be generated during pumping.
Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk.
The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.
Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

Packaging material : Suitable material: For containers, or container linings use mild steel, stainless steel., Aluminium may also be used for applications where it does not present an unnecessary fire hazard., Examples of suitable materials are: high density polyethylene (HDPE) and Viton (FKM), which have been specifically tested for compatibility with this product., For container linings, use amine-adduct cured epoxy paint., For seals and gaskets use: graphite, PTFE, Viton A, Viton B.
Unsuitable material: Some synthetic materials may be unsuitable for containers or container linings depending on the material specification and intended use. Examples of materials to avoid are: natural rubber (NR), nitrile rubber (NBR), ethylene propylene rubber (EPDM), polymethyl methacrylate (PMMA), polystyrene, polyvinyl chloride (PVC), polyisobutylene., However, some may be suitable for glove materials.

Container Advice : Containers, even those that have been emptied, can contain explosive vapours. Do not cut, drill, grind, weld or perform

Safety Data Sheet

Shell Special Fuel Oil

Version 2.0

Revision Date 22.07.2015

Print Date 23.07.2015

similar operations on or near containers.

Specific use(s) : Not applicable

See additional references that provide safe handling practices for liquids that are determined to be static accumulators: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices on Static Electricity).
CENELEC CLC/TR 50404 (Electrostatics – Code of practice for the avoidance of hazards due to static electricity).

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
hydrogen sulphide	7783-06-4	TWA	10 ppm 15 mg/m ³	PH OEL
		CEIL	20 ppm	OSHA Z-2
		Peak	50 ppm	OSHA Z-2
		TWA	1 ppm	ACGIH
		STEL	5 ppm	ACGIH

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods
<http://www.cdc.gov/niosh/>

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods
<http://www.osha.gov/>

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances
<http://www.hse.gov.uk/>

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany
<http://www.dguv.de/inhalt/index.jsp>

L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

Engineering measures : The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances.

Safety Data Sheet

Shell Special Fuel Oil

Version 2.0

Revision Date 22.07.2015

Print Date 23.07.2015

Appropriate measures include:
Use sealed systems as far as possible.
Firewater monitors and deluge systems are recommended.
Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.
Local exhaust ventilation is recommended.
Eye washes and showers for emergency use.

General Information:

Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when there is potential for inhalation; clear up spills immediately and dispose of wastes safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.
Do not ingest. If swallowed then seek immediate medical assistance

Personal protective equipment

Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory protection : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. All respiratory protection equipment and use must be in accordance with local regulations.

Select a filter suitable for the combination of organic gases and vapours [Type A/Type P boiling point >65°C (149°F)].

Hand protection
Remarks

: Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves,

Safety Data Sheet

Shell Special Fuel Oil

Version 2.0

Revision Date 22.07.2015

Print Date 23.07.2015

hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material.

Select gloves tested to a relevant standard (e.g. Europe EN374, US F739). When handling heated product wear heat resistant gloves. When prolonged or frequent repeated contact occurs, Nitrile gloves may be suitable. (Breakthrough time of > 240 minutes.) For incidental contact/splash protection Neoprene, PVC gloves may be suitable.

- Eye protection : Wear goggles for use against liquids and gas. If a local risk assessment deems it so then chemical splash goggles may not be required and safety glasses may provide adequate eye protection.
- Skin and body protection : Wear chemical resistant gloves/gauntlets and boots. Where risk of splashing, also wear an apron.
- Thermal hazards : When handling heated product, wear heat resistant gloves, safety hat with visor, heat resistant coveralls (with cuffs over gloves and legs over boots), and heavy duty boots, e.g. leather for heat resistance.
- Hygiene measures : Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Environmental exposure controls

- General advice : Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour. Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Chapter 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant

Safety Data Sheet

Shell Special Fuel Oil

Version 2.0

Revision Date 22.07.2015

Print Date 23.07.2015

before discharge to surface water.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: Not applicable
Odour	: Not applicable
Odour Threshold	: Data not available
pH	: Not applicable
Melting point/freezing point	: Data not available
Boiling point/boiling range	: ≥ 150 °C / ≥ 302 °F Method: Unspecified
Flash point	: 61 - 200 °C / 142 - 392 °F Method: Unspecified
Evaporation rate	: Data not available
Flammability (solid, gas)	: Not applicable
Upper explosion limit	: 5 %(V)
Lower explosion limit	: Typical 0.5 %(V)
Vapour pressure	: ≤ 0.4 kPa (38.0 °C / 100.4 °F) Method: Unspecified
Relative vapour density	: Data not available
Relative density	: Data not available
Density	: 985.0 kg/m ³ (15.0 °C / 59.0 °F) Method: Unspecified
Solubility(ies)	
Water solubility	: negligible
Solubility in other solvents	: Data not available
Partition coefficient: n-octanol/water	: log Pow: 3 - 6
Auto-ignition temperature	: > 220 °C / 428 °F
Decomposition temperature	: Data not available
Viscosity	
Viscosity, kinematic	: 100 - 275 mm ² /s (50.0 °C / 122.0 °F) Method: Unspecified

Safety Data Sheet

Shell Special Fuel Oil

Version 2.0

Revision Date 22.07.2015

Print Date 23.07.2015

Explosive properties	: Classification Code: Not classified
Oxidizing properties	: Not applicable
Conductivity	: Low conductivity: < 100 pS/m, The conductivity of this material makes it a static accumulator., A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10 000 pS/m., Whether a liquid is nonconductive or semiconductive, the precautions are the same., A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid

10. STABILITY AND REACTIVITY

Chemical stability	: Stable under normal conditions of use.
Conditions to avoid	: Avoid heat, sparks, open flames and other ignition sources. In certain circumstances product can ignite due to static electricity.
Incompatible materials	: Strong oxidising agents.
Hazardous decomposition products	: Hazardous decomposition products are not expected to form during normal storage. Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

11. TOXICOLOGICAL INFORMATION

Basis for assessment	: Information given is based on product data, a knowledge of the components and the toxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
Information on likely routes of exposure	: Skin and eye contact are the primary routes of exposure although exposure may occur through inhalation or following accidental ingestion.

Acute toxicity

Product:

Safety Data Sheet

Shell Special Fuel Oil

Version 2.0

Revision Date 22.07.2015

Print Date 23.07.2015

Acute oral toxicity	:	LD50 Oral Rat: > 5,000 mg/kg Remarks: Low toxicity:
Acute inhalation toxicity	:	LC 50 Rat: >1 - <=5 mg/l Exposure time: 4 h Remarks: Harmful if inhaled.
Acute dermal toxicity	:	LD 50 Rabbit: > 2,000 mg/kg Remarks: Low toxicity:
Acute toxicity (other routes of administration)	:	Remarks: Inhalation of vapours or mists may cause irritation to the respiratory system.

Skin corrosion/irritation

Product:

Remarks: Expected to be slightly irritating., Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis., Contact with hot material can cause thermal burns which may result in permanent skin damage.

Serious eye damage/eye irritation

Product:

Remarks: Expected to be slightly irritating., Hot product may cause severe eye burns and/or blindness.

Remarks: Irritating to eyes. (Hydrogen Sulfide)

Respiratory or skin sensitisation

Product:

Remarks: Not expected to be a sensitiser.

Germ cell mutagenicity

Product:

	:	Remarks: Positive in in-vitro, but negative in in-vivo mutagenicity assays.
Germ cell mutagenicity-Assessment	:	This product does not meet the criteria for classification in categories 1A/1B.

Carcinogenicity

Product:

Remarks: Causes cancer in laboratory animals.

Carcinogenicity - Assessment	:	Category 1B
------------------------------	---	-------------

Safety Data Sheet

Shell Special Fuel Oil

Version 2.0

Revision Date 22.07.2015

Print Date 23.07.2015

Material	GHS/CLP Carcinogenicity Classification
fuel oil, residual	Carcinogenicity Category 1B

Reproductive toxicity

Product:

: Remarks: Causes foetotoxicity at doses which are maternally toxic.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

STOT - single exposure

Product:

Remarks: Contains hydrogen sulphide., Inhalation of vapours or mists may cause irritation to the respiratory system.

STOT - repeated exposure

Product:

Remarks: May cause damage to organs or organ systems through prolonged or repeated exposure.

Target Organs: Blood, Liver, thymus

Aspiration toxicity

Product:

Not considered an aspiration hazard.

Further information

Product:

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

12. ECOLOGICAL INFORMATION

Basis for assessment : Fuels are typically made from blending several refinery streams. Ecotoxicological studies have been carried out on a variety of hydrocarbon blends and streams but not those containing additives.

Safety Data Sheet

Shell Special Fuel Oil

Version 2.0

Revision Date 22.07.2015

Print Date 23.07.2015

Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Ecotoxicity

Product:

- Toxicity to fish (Acute toxicity) : Remarks: Harmful:
LL/EL/IL50 >10 <= 100 mg/l
- Toxicity to crustacean (Acute toxicity) : Remarks: Toxic:
LL/EL/IL50 > 1 <= 10 mg/l
- Toxicity to algae/aquatic plants (Acute toxicity) : Remarks: Very toxic:
LL/EL/IL50 < 1 mg/l
- Toxicity to fish (Chronic toxicity) : Remarks: NOEC/NOEL expected to be > 0.01 - <= 0.1 mg/l (based on modeled data)
- Toxicity to crustacean (Chronic toxicity) : Remarks: NOEC/NOEL expected to be > 0.1 - <= 1.0 mg/l (based on modeled data)
- Toxicity to microorganisms (Acute toxicity) : Remarks: Expected to be practically non toxic:
LL/EL/IL50 > 100 mg/l

Persistence and degradability

Product:

- Biodegradability : Remarks: The volatile constituents will oxidize rapidly by photochemical reactions in air., Major constituents are inherently biodegradable.

Bioaccumulative potential

Product:

- Bioaccumulation : Remarks: Contains constituents with the potential to bioaccumulate.
- Partition coefficient: n-octanol/water : log Pow: 3 - 6

Mobility in soil

Product:

- Mobility : Remarks: Floats on water., Contains volatile components., Partly evaporates from water or soil surfaces, but a significant proportion will remain after one day., Large volumes may penetrate soil and could contaminate groundwater.

Other adverse effects

Product:

Safety Data Sheet

Shell Special Fuel Oil

Version 2.0

Revision Date 22.07.2015

Print Date 23.07.2015

- Results of PBT and vPvB assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB.
- Additional ecological information : Films formed on water may affect oxygen transfer and damage organisms.

13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Recover or recycle if possible.
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.
Do not dispose into the environment, in drains or in water courses
Do not dispose of tank water bottoms by allowing them to drain into the ground.
Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.
- Contaminated packaging : Send to drum recoverer or metal reclaimer.
Drain container thoroughly.
After draining, vent in a safe place away from sparks and fire.
Residues may cause an explosion hazard if heated above the flash point. Do not puncture, cut or weld uncleaned drums.
Do not pollute the soil, water or environment with the waste container.
Comply with any local recovery or waste disposal regulations.

14. TRANSPORT INFORMATION

International Regulation

- ADR**
- UN number : 3082
- Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Fuel oil, residual, Heavy fuel oil)
- Class : 9
- Packing group : III
- Labels : 9
- Hazard Identification Number : 90
- Environmentally hazardous : yes
- IATA-DGR**
- UN/ID No. : UN 3082

Safety Data Sheet

Shell Special Fuel Oil

Version 2.0

Revision Date 22.07.2015

Print Date 23.07.2015

H410

Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	Acute toxicity
Aquatic Acute	Acute aquatic toxicity
Aquatic Chronic	Chronic aquatic toxicity
Asp. Tox.	Aspiration hazard
Carc.	Carcinogenicity
Flam. Liq.	Flammable liquids
Repr.	Reproductive toxicity
STOT RE	Specific target organ toxicity - repeated exposure

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

Further information

Other information : This product is intended for use in closed systems only.

Due to the conversion of this product to GHS classification and labelling, there has been a significant change to the nature of the information presented in chapter 2.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.